

D 38 RLE



4 gears and 2000 W

for drilling into steel, wood and plastic materials or as drive motor

D 38 RLE applications

- Steel and metal structures
- Wooden structures
- Drive motor for a wide range of applications

D 38 RLE features

- Broad speed range thanks to 4-speed gearbox
- Short and compact overall length (approx. 280 mm)
- Trigger lock for continuous use
- Precision tool holder for exact concentricity and high power transmission
- Powerful, robust 2000 W motor with clockwise/anticlockwise rotation
- Electronic for constant speed control
- Speed infinitely adjustable with adjusting dial in every gear
- Very high torque in 1st gear (> 250 Nm)
- Maintenance-free 4-speed gearbox with lifetime lubrication
- Large dimensioned tool holder of dia. 70 mm
- User-friendly positioning of clockwise/anticlockwise selector switch and speed regulator
- Light alloy housing



Rated power	2000 W
Drilling range in	
steel with drill bit	up to dia. 32 mm
wood with drill bit	up to dia. 130 mm
polypropylene with LS core cutter	up to dia. 600 mm
Rated speed 1st/2nd/3rd/4th gear	120/210/380/650 rpm
Machine weight	8.6 kg
Tool holder	MK 3 morse taper

Order-No. D 38 RLE

Standard specification: DUSS D 38 RLE 4-speed rotary drill, taper drift.

ACCESSORIES

D 38 RLE



Magnet drill stand for mounting of D 38 RLE 4-speed rotary drill

Rated power	70 W	Spiral drill bit	up to dia. 32 mm
Clamping	dia. 70 mm	Core drill	up to dia. 150 mm
Stroke	290 mm	Positioning device	yes
Cable length	4 m	Swivel range	346°
Socket outlet	up to 16 A	Shift range	+/- 10 mm
Magnetic attraction*	up to 25.000 N	Contact surface	200 x 100 mm
Height	570 mm	Weight	25 kg

Order-No. MAG80-D38

* Pull-of method to VDE 0580, tested and minuted



Attachement clutch

for safe and hand-held drilling, maximum operating torque 200 Nm, MK 3 morse taper shank, socket holder with 1/2" square

Order-No. VSKU



Screw handle

for safe and hand-held application

Order-No. D38-SH



MK3/MK2 reduction sleeve

for tools with MK 2 morse taper

Order-No. D 324



MK3/MK1 reduction sleeve

for tools with MK 1 morse taper

Order-No. D 323



MK 3 chuck arbor

for F 13 three-jaw chuck

Order-No. D 322



Three-jaw chuck

clamping range 1 - 13 mm, for adaption of drills with cylindrical shank, screw bits, etc.

Order-No. F 13

Subject to technical changes without notice · 04/2014